

## Transforming Technologies

# CL-SP1000 Series

## Anti Static Cellulose Tape w/ ESD Symbol

### Description

Transforming Technologies ESD safe clear cellulose tape with ESD Symbols is hand tearable and biodegradable. It is coated with a Solvent Based Natural Rubber Adhesive which provided excellent tack and holding power. Used for general purpose mending, binding packaging and carton sealing. Meets Specification No. CID-AA-113B, Type 1, Class A. Meets or exceeds requirements of ANSI ESD-S20.20.



- **Strong Adhesion**
- **Four (4) Standard Widths**
- **ESD Symbol**


### Product Specifications

Backing:	35 micron Pure Cellulose
Thickness:	2.0 mils (.050mm)
Adhesive:	Solvent Based Natural Rubber
Adhesion:	34 oz/inch
Ball Tack(J Dow Method):	20#
Holding Strength:	1/32" per 2 hours
-SST Plate; 1/2" x 1"; 1 kg. load	
Tensile Strength:	24lbs/inch
Elongation:	22% at break
Temperature Resistance:	32°F to 150°F (0°C to 66°C)

### Product Number

<u>Item Number</u>	<u>Description</u>
CL1200-P	1/2" (12mm) x 72 yards
CL1801-P	3/4"(18mm) x 72 yards
CL2402-P	1" (24mm) x 72 yards
CL4803-P	2" (48mm) x 72 yards

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.



**Transforming Technologies, LLC**

3407 Silica Rd.  
Sylvania, OH 43560

Phone: 1.419.841.9552

Fax: 1.419.841.3241

[www.transforming-technologies.com](http://www.transforming-technologies.com)

*Outstanding Alternatives in Static Control*